

Maytag® Dryer Specifications

Maytag Neptune®

Maytag Atlantis™


Maytag Performa®

Exterior Color Options

FEATURES	MDE/G7500	MDE/G5500	MDE/G4000	MDE/G8600	MDE/G7600	MDE/G6200	MDE/G3500	MDE/G2500	PYE/G2300
Capacity	Oversize Capacity Plus			Oversize Capacity Plus			Oversize Capacity		
Controls	LCD	LED	Push Button	Push Button	Push Button	Push Button	Rotary	Rotary	Rotary
Dryness Control	IntelliDry™	IntelliDry™	IntelliDry™	IntelliDry™	IntelliDry™	Automatic	IntelliDry™	Automatic	Automatic
Moisture Monitor	■		■	■	■		■		
Adjustable Degree Of Dryness	■	■	■	■	■	■	■	■	■
Temperature Settings	5	5	Infinite	Infinite	4	4	4	4	3
Sound-Silencing Package	EQ™ Plus	EQ™ Plus	EQ™ Plus	Quiet Plus II	Quiet Plus	Quiet Pack	Quiet Pack	Quiet Pack	Quiet Pack
Time Dry	■	■	■	■	■	■	■	■	■
Air Fluff	■	■	■	■	■	■	■	■	■
Damp Dry Cycle	■	■	■	■	■	■	■	■	■
Press Care/Wrinkle Prevent	On/Off	On/Off	On/Off	■	■	■	■	■	■
Wrinkle Release	■	■	■	■	■	■	■	■	■
Wrinkle-Free Fabrics Cycle	■	■	■	■	■	■	■	■	■
Delicates Temp. Setting	■	■	■	■	■	■	■	■	■
Easy Care Permanent Press	■	■	■	■	■	■	■	■	■
End-Of-Cycle Chime	Adjustable	Adjustable	On/Off	Adjustable	■	Signal	On/Off	■	■
Time Remaining Indicator	■	■	■	■	■	■	■	■	■
Drum Light	■	■	■	■	■	■	■	■	■
Ultra Care (Extra Low) Temp.	■	■	■	■	■	■	■	■	■
Dryer® Cycle	■	■	■	■	■	■	■	■	■
Drying Rack	■	■	■	■	■	■	■	■	■
Remind Chime	■	■	■	■	■	■	■	■	■
Damp Dry Chime	■	■	■	■	■	■	■	■	■
Freshen-Up Cycle	■	■	■	■	■	■	■	■	■
Smart Cool Down	■	■	■	■	■	■	■	■	■
Trilingual Navigator	■	■	■	■	■	■	■	■	■
Control Panel Lockout	■	■	■	■	■	■	■	■	■
Extra-Large Door Opening	■	■	■	■	■	■	■	■	■
DuraCushion™ Dryer Drum	■	■	■	■	■	■	■	■	■
High-Capacity Blower	■	■	■	■	■	■	■	■	■
4-Point Suspension System	■	■	■	■	■	■	■	■	■
Electronic Ignition W/Safety Shut-Off Valve (Gas Only)	■	■	■	■	■	■	■	■	■
Color Availability	White/Bisque	White/Bisque	White/Bisque	White/Bisque	White/Bisque	White/Bisque	White/Bisque	White	White




White



Bisque



MAYTAG NEPTUNE® DRYERS



MAYTAG NEPTUNE® DRYERS

MOTOR: 1/4 HP, 120 volt, 60 Hz, single-phase, thermally protected against overload, auto-reset.

EXHAUST: Use a minimum of 4" (10.2 cm) diameter rigid aluminum or galvanized steel duct. Never use plastic, nonmetal or combustible duct.

HEAT SOURCE/ELECTRICAL REQUIREMENTS:


Electric model — 5,300 watt nichrome helix coil; 240 volt, AC, 60 Hz; 30 amp fuse.

Gas model — Single port burner with automatic electric ignition; 22,000 BTU/hr. 15 amp fuse. Self-adjusting valve automatically compensates for variation in gas pressure.

WEIGHTS (Crated / Uncrated):

145 lbs. (66 kg)/130 lbs. (59 kg).

MAYTAG ATLANTIS™ DRYERS



MAYTAG ATLANTIS™ DRYERS

MOTOR: 1/4 HP, 120 volt, 60 Hz, single-phase, thermally protected against overload, auto-reset.

EXHAUST: Use a minimum of 4" (10.2 cm) diameter rigid aluminum or galvanized steel duct. Never use plastic, nonmetal or combustible duct.

HEAT SOURCE/ELECTRICAL REQUIREMENTS:


Electric model — 5,300 watt nichrome helix coil; 240 volt, AC, 60 Hz; 30 amp fuse.

Gas model — Single port burner with automatic electric ignition; 22,000 BTU/hr. 15 amp fuse. Self-adjusting valve automatically compensates for variation in gas pressure.

WEIGHTS (Crated / Uncrated):

145 lbs. (66 kg)/130 lbs. (59 kg).

MAYTAG PERFORMA® DRYERS M Series



MAYTAG PERFORMA® DRYERS

MOTOR: 1/4 HP, 120 volt, 60 Hz, single-phase, thermally protected against overload, auto-reset.

EXHAUST: Use a minimum of 4" (10.2 cm) diameter rigid aluminum or galvanized steel duct. Never use plastic, nonmetal or combustible duct.

L SERIES

HEAT SOURCE/ELECTRICAL REQUIREMENTS:


Electric model — 5,300 watt nichrome helix coil; 240 volt, AC, 60 Hz; 30 amp fuse.

Gas model — Single port burner with automatic electric ignition; 22,000 BTU/hr. 15 amp fuse. Self-adjusting valve automatically compensates for variation in gas pressure.

WEIGHTS (Crated / Uncrated):

145 lbs. (66 kg)/130 lbs. (59 kg).

MAYTAG PERFORMA® DRYERS P Series



P SERIES

HEAT SOURCE/ELECTRICAL REQUIREMENTS:

Electric model — 4,750 watt nichrome helix coil; 240 volt, AC, 60 Hz; 30 amp fuse.

Gas model — Single port burner with automatic electric ignition; 18,000 BTU/hr. 15 amp fuse. Self-adjusting valve automatically compensates for variation in gas pressure.

WEIGHTS (Crated / Uncrated):

Electric: 114 lbs. (52 kg)/102 lbs. (46 kg). Gas: 121 lbs. (55 kg)/109 lbs. (49 kg).



Gas dryer dimensions are shown. Electric dryer dimensions are identical to the gas model. Electric models do not have the gas manifold connections or the power cord. Terminal block on electric models only.

*Dimensions will vary according to adjustment of leveling legs.

**Includes 3/4" for hinge on back of washer/dryer.

U.S. Department of Energy
U.S. Environmental Protection Agency
Models MAH7500, MAH5500A, MAH5500B and MAV9600